

Li-Ion Batteries >100 Wh

Safety information for Lithium-Ion batteries

Date of issue: 05/02/2015

Revision date: 27/07/2015

Supersedes: 27/01/2015

Version: 5.4

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Trade name Hilti B 18 / 5.2 Li-Ion, Hilti B 22 / 5.2 Li-Ion, Hilti B 36 / 3.0 Li-Ion, Hilti B 36 / 3.3 Li-Ion, Hilti B 36 / 3.9 Li-Ion, Hilti B 36 / 5.2 Li-Ion, Hilti B 36 / 6.0 Li-Ion

Relevant identified uses of the substance or mixture and uses advised against

No additional information available

Manufacturer/Supplier

Supplier

Hilti (Aust.) Pty. Ltd.
Level 5, 1G Homebush Bay Drive
2138 Rhodes - Australia
T +61 131 292 - F +61 1300 135 042
serviceaustralia@hilti.com

Department issuing data specification sheet

Hilti Entwicklungsgesellschaft mbH
Hiltistrasse 6
86916 Kaufering - Deutschland
T +49 8191 906310 - F +49 8191 90176310
anchor.hse@hilti.com

SECTION 2: Hazards identification

For the battery chemical materials are stored in a hermetically sealed metal case, designed to withstand temperatures and pressures encountered during normal use. As a result, during normal use there is no physical danger of ignition or explosion and chemical danger of hazardous materials leakage.

It may cause heat generation or electrolyte leakage if battery terminals contact with other metals. Electrolyte is flammable. In case of electrolyte leakage move the battery from fire immediately.
However if exposed to a fire, added mechanical shocks, decomposed, added electric stress by miss-use, the gas release vent will be operated. The battery case will be broken at the extreme, hazardous materials may be released.

Moreover, if heated strongly by a surrounding fire, acrid gas may be emitted.

SECTION 3: Composition/information on ingredients

Lithium Ion rechargeable battery pack:

Name/Type	Energy content (Wh)
Hilti B 18 / 5.2 Li-Ion	112,4
Hilti B 22 / 5.2 Li-Ion	112,4
Hilti B 36 / 3.0 Li-Ion	108
Hilti B 36 / 3.3 Li-Ion	118,8
Hilti B 36 / 3.9 Li-Ion	140
Hilti B 36 / 5.2 Li-Ion	187,2
Hilti B 36 / 6.0 Li-Ion	216

This product contains a positive electrode (Lithium cobalt oxide), a negative electrode (graphite) and electrolyte (ethylene carbonate, diethyl carbonate and lithium hexafluorophosphate).

The physical form of the product, however, precludes exposure to workers under normal conditions of use.

SECTION 4: First aid measures

Description of first aid measures

First-aid measures general	If the electrolyte is leaking out of the battery pack, the following measures have to be taken.
First-aid measures after inhalation	Allow breathing of fresh air. Allow the victim to rest.
First-aid measures after skin contact	Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist.
First-aid measures after ingestion	Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

Li-Ion Batteries >100 Wh

Safety information for Lithium-Ion batteries

SECTION 7: Handling and storage

Precautions for safe handling

Precautions for safe handling

Do not soak in water or seawater.
 Do not expose to strong oxidizers.
 Do not give a strong mechanical shock or fling.
 Never disassemble, modify or deform.
 Do not connect the positive terminal to the negative terminal with electrically conductive material.
 Use only the chargers / electric tools specified by Hilti to charge or discharge the battery.

Do not throw into fire or expose to high temperatures (>85 °C).
 Do not connect the positive terminal to the negative terminal with electrically conductive material.

Hygiene measures

Always wash hands after handling the product.

Conditions for safe storage, including any incompatibilities

Storage conditions

Avoid direct sunlight, high temperature, high humidity.
 Store in a cool place (temperature: -20 °C ~ 35 °C, humidity: 45 - 85%).

Incompatible products

Strong bases. Strong acids.

Incompatible materials

Sources of ignition. Direct sunlight.

Storage temperature

-20 - 35 °C

Prohibitions on mixed storage

Store away from water.
 Do not store together with electrically conductive materials.

The accu-pack should be stored at 30 to 50% of the charging capacity.
 Avoid storing in places where it is exposed to static electricity.

SECTION 8: Exposure controls/personal protection

Exposure controls

Appropriate engineering controls

If the electrolyte is leaking out of the battery pack, the following measures have to be taken.

Personal protective equipment

Avoid all unnecessary exposure.

Hand protection

Wear protective gloves

Type	Material	Permeation	Thickness (mm)	Standard
Disposable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	0,12	EN 374

Eye protection

Chemical goggles or safety glasses



Other information

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance

plastic case.

Colour

red. Black.

Explosive properties

Risk of explosion by shock, friction, fire or other sources of ignition.

Li-Ion Batteries >100 Wh

Safety information for Lithium-Ion batteries

Other information

No additional information available

SECTION 10: Stability and reactivity

Reactivity

No additional information available

Chemical stability

Stable under normal conditions.

Possibility of hazardous reactions

Heating may cause a fire or explosion.

Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Water, humidity.

Incompatible materials

Conductive materials, water, seawater, strong oxidizers and strong acids.

Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

Information on toxicological effects

Potential adverse human health effects and symptoms

This product contains an organic electrolyte. If the electrolyte is leaking out of the battery pack, the following effects are known when getting into contact: Irritation: severely irritant to eyes. Irritation: may cause irritation to the respiratory system.

Other information

When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

SECTION 12: Ecological information

Additional information

Do not allow battery packs to penetrate the soil.
The battery cell may corrode and electrolyte may leak.

SECTION 13: Disposal considerations

Waste treatment methods

Waste disposal recommendations

Dispose in a safe manner in accordance with local/national regulations. Refer to manufacturer/supplier for information on recovery/recycling.

Ecology - waste materials

Avoid release to the environment.





SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	RID
UN number			
3480	3480	3480	3480

Li-Ion Batteries >100 Wh

Safety information for Lithium-Ion batteries

ADR	IMDG	IATA	RID
UN proper shipping name			
LITHIUM ION BATTERIES	LITHIUM ION BATTERIES	Lithium ion batteries	LITHIUM ION BATTERIES
Transport document description			
UN 3480 LITHIUM ION BATTERIES, 9, (E)	UN 3480 LITHIUM ION BATTERIES, 9		
Transport hazard class(es)			
9	9	9	9
			
Packing group			
Not applicable	Not applicable	Not applicable	Not applicable
Environmental hazards			
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	Dangerous for the environment : No
No supplementary information available			

Special precautions for user

- Overland transport

Classification code (ADR)	M4
Special provisions (ADR)	230, 636b, 376, 377
Limited quantities (ADR)	0
Packing instructions (ADR)	P903, P908, P909
Tunnel restriction code (ADR)	E

- Transport by sea

Special provisions (IMDG)	230b, 376, 377
Limited quantities (IMDG)	0
Packing instructions (IMDG)	P903, P908, P909
EmS-No. (Fire)	F-A
EmS-No. (Spillage)	S-I
Stowage category (IMDG)	A
MFAG-No	147

- Air transport

PCA packing instructions (IATA)	965
PCA max net quantity (IATA)	5kg
Special provisions (IATA)	A88, A99, A154, A164, A183

- Rail transport

Special provisions (RID)	230, 636b, 376, 377
Limited quantities (RID)	0
Packing instructions (RID)	P903, P908, P909
Carriage prohibited (RID)	No

Li-Ion Batteries >100 Wh

Safety information for Lithium-Ion batteries

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No additional information available

SECTION 15: Regulatory information

No additional information available

SECTION 16: Other information

No additional information available

Safety information for Lithium-Ion batteries

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product